Lith™

LITHIUM BROMIDE, Molybdate Inhibited

55% w/w Solution

CAS Number: 7550-35-8
Chemical Formula: LiBr

PRODUCT DESCRIPTION

Lithium Bromide Molybdate Inhibited 55% Solution is a concentrated aqueous lithium bromide solution containing lithium molybdate as a corrosion inhibitor. It is designed for use in absorption refrigeration and air-conditioning systems, where lithium bromide absorbs water vapour to support the cooling cycle. The molybdate inhibitor helps provide corrosion protection for compatible system components.

KEY FEATURES

- Lithium bromide concentration of 54.5–55.5% by weight
- Contains lithium molybdate corrosion inhibitor
- High affinity for water vapour
- Clear to slightly hazy, colourless aqueous solution
- Suitable for absorption-based cooling systems
- Controlled levels of specified inorganic impurities

APPLICATIONS

- Absorption chillers using water as the refrigerant
- Industrial air-conditioning systems
- Absorption refrigeration systems
- Moisture absorption in industrial cooling applications

CHEMPORT
Specialty Chemical Experts

LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or thirdparty rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61 2 9410 3317
info@chemport.com.au

Suite 2.08
32 Delhi Road
Macquarie Park
NSW 2113
Australia

chemport.com.au

PRODUCT SPECIFICATIONS

PARAMETER	TYPICAL VALUE
Appearance	Clear or slightly hazy, colourless aqueous solution
Lithium Bromide (LiBr), wt.%	54.5–55.5
Lithium Molybdate (Li_2MoO_4), wt.%	0.013–0.017
Calcium (Ca)	≤20 ppm
Magnesium (Mg)	≤10 ppm
Sulfate (SO_4), wt.%	≤0.02
Chloride (Cl), wt.%	≤0.05
Alkalinity (as LiOH), N	0.06–0.07
Insoluble Solids, wt.%	≤0.01
Density at 20°C	1.6 g/mL
Foaming	Passes test

PACKAGING

Available in 25 kg drums and 1,000 kg intermediate bulk containers (IBCs). Alternative packaging options may be available upon request.

STORAGE & HANDLING

Store in tightly sealed, corrosion-resistant containers in a cool, dry, well-ventilated area. Keep containers closed when not in use and protect from contamination. Avoid prolonged contact with skin and eyes. In the event of skin contact, rinse immediately with plenty of water.

SAFETY

Harmful if swallowed and may cause irritation to the eyes and respiratory system. Avoid ingestion and direct contact with skin and eyes. Wear appropriate personal protective equipment, including chemical-resistant gloves and safety glasses.

Refer to the current Safety Data Sheet (SDS) for detailed information on hazards, safe handling, storage, transport and disposal.