# SILANOX™ L234A

Polyether-Modified Silicone Additive

## PRODUCT DESCRIPTION

SILANOX™ L234A is a 100% active polyether-modified silicone additive designed for use in both solvent-based and water-based coating systems.

It provides excellent slip and levelling performance while supporting anti-crater and anti-blocking properties. SILANOX™ L234A also promotes effective orientation of matting powders in coating formulations.

## KEY FEATURES

- Excellent slip performance
- Promotes smooth and uniform levelling
- Anti-crater properties
- Supports anti-blocking performance
- Excellent matting powder orientation
- Suitable for water-based and solvent-based coatings
- 100% active ingredient content

## APPLICATIONS

- Water-based coatings
- Solvent-based coatings
- Matt and low-gloss coating systems
- Coating formulations requiring improved slip and levelling
- Systems requiring anti-crater and anti-blocking performance

CHEMPORT
Specialty Chemical Experts

LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or thirdparty rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Suite 2.08
32 Delhi Road
Macquarie Park
NSW 2113
Australia

chemport.com.au

**PRODUCT SPECIFICATIONS**

| PARAMETER | TYPICAL VALUE |
|---|---|
| Appearance | Colourless to light yellow liquid |
| Composition | Polyether-modified silicone |
| Active Ingredient Content | 100% |

## RECOMMENDED DOSAGE
Typical addition level is 0.1–1.0% of the total formulation.

## PACKAGING
Available in 25 kg and 200 kg drums.

## STORAGE & HANDLING
Store sealed under normal storage conditions. Refer to the current Safety Data Sheet for additional information on safe handling and storage.

## SHELF LIFE
24 months when stored at normal temperature.

## SAFETY
Refer to the current Safety Data Sheet for detailed information on safe handling, storage, personal protection and disposal.