THIXO LW67

DESCRIPTION

THIXO LW67 is a specialty additive designed to control Thixotropy, sag resistance, open time, and workability in cementitious formulations. The product is particularly suited to lightweight ceramic tile adhesives and provides improved application properties, enhanced adhesion, and extended open time performance. It is compatible with hybrid binder systems and a wide range of drymix additives.

KEY FEATURES

- Improves anti-sag performance during application
- Enhances workability and trowelling smoothness
- Supports extended open time and wet edge retention
- Contributes to improved adhesion and cohesive film formation
- Easily disperses in dry blends
- Compatible with hybrid binder systems
- Ideal for lightweight ceramic tile adhesives

APPLICATIONS

- Cement-based systems
- Ceramic tile adhesives
- Mortars and repair mortars
- Renders
- Drymix construction materials

TYPICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Appearance	Free-Flowing Powder
Application Type	Rheology & Anti-Sag Additive
Recommended Dosage	1.0 – 2.0%
Addition Method	Dry Blend Addition

CHEMPORT
Specialty Chemical Experts

LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Suite 2.08
32 Delhi Road
Macquarie Park
NSW 2113
Australia

chemport.com.au

PACKAGING

Available in 20 kg bags.

STORAGE & HANDLING

Store in a cool, dry location away from moisture. Keep bags tightly sealed when not in use. When stored correctly in unopened packaging, the product maintains stability for an extended period. Avoid conditions that may cause lumping or product degradation.

SAFETY

Use standard industrial hygiene practices when handling powders. Avoid inhalation and contact with eyes or skin. Appropriate PPE including gloves, dust masks, and safety eyewear is recommended. Refer to the Safety Data Sheet (SDS) for detailed safety and handling information.