METHOD™ CMC HV

Sodium Carboxymethyl Cellulose

METHOD™ CMC HV is a high-viscosity sodium carboxymethyl cellulose designed for use as a fluid-loss control additive in drilling fluids and oilwell cementing applications. It helps reduce free water and prevent solids settlement while providing effective filtrate control.

The product has a relatively strong retarding effect on cement and is suitable for shallow-well applications with bottom-hole temperatures up to 100°C. Laboratory testing is recommended when used in cementing slurry formulations.

KEY FEATURES

- Good filtrate control
- High retarding effect
- Moderate calcium resistance
- High-viscosity grade
- Helps reduce free water and solids settlement

APPLICATIONS

- Drilling fluids
- Oilwell cementing
- Fluid-loss control
- Shallow-well applications
- Salt-water drilling fluid systems

PRODUCT SPECIFICATIONS

Parameter	Specification
Appearance	White Powder
Chemical Basis	Sodium Carboxymethyl Cellulose
Filtrate Loss of Saturated Salt-Water Suspension	≤ 10 mL
Starch or Starch Derivatives	None
Organic Chlorine (%)	0.00
Recommended Dosage (%)	0.20–0.45

CHEMPORT
Specialty Chemical Experts

LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or thirdparty rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Suite 2.08
32 Delhi Road
Macquarie Park
NSW 2113
Australia

chemport.com.au

PACKAGING
Available in 25 kg net paper bags with polyethylene inner liner.

STORAGE
Store under dry and clean conditions away from direct sunlight. Keep packaging securely closed and protect from moisture during storage and handling.

SHELF LIFE
2 years from the date of production when stored under recommended conditions.

SAFETY

Refer to the relevant Safety Data Sheet (SDS) before handling or use.